







P 2 0 0 6 T M K II N83 V A / S N 3 6 0

PRICE \$687,920



Flexible and economical, Tecnam P2006T is a twin-engine four-seat aircraft with fully retractable landing gear with a class of its own. The superior high-wing configuration offers stability, superior cabin visibility and easy access for passengers and luggage. Tecnam has used its extensive experience with aluminum airframes to create in the Tecnam P2006 a robust yet very light airframe, resulting in an outstanding payload-to-total weight ratio.



GARMIN G950 NXI S-TEC 55X AUTOPILOT

SPECIAL PAINT



PREMIUM INTERIOR



SURROUND VIEW WINDOWS



STANDARD EQUIPMENT

Garmin G1000 NXi

G1000 Nxi Integrated Flight Deck System includes:

- GDU 1050 10-inches PFD
- GDU 1054 10-inches MFD
- . Dual GED 71B Engine & Airframe unit
- Dual GIA 64 WAAS Com/nav/GPS/GS/Loc
- GMA1360 Digital audio system
- GMU44 Magnetometer
- GDC72 Air data computer
- GRS79 OAT
- GTX345R Mode S Transponder (ADS-B In
- and OUT)
 - S-TEC 55 dual Axis Autopilot with Electric
- Trim

Flight instruments and indicators

- Magnetic Compass
- MD 302 Standby Attitude Module
- Pitot System Heated
- . Static System
- Alternate Static Source
- Stall Warning Audible
- Stabilator Trim Position Indicator
- Rudder Trim Position Indicator

Flight Conttrols

- Hydraulic Toe Brakes
- Parking Brake
- Electric Flap
- Dual Flight Controls
- Steerable Nose Wheel
- Aileron Lock
- Stabilator Trim (Manual)
- Engine Controls:
 - o Throttle, Two
 - o Propellers, Two
 - o Carburetor Heat, Two
 - Choke, Two
- Flight Trim Controls:
 - o Rudder with Indicator
 - o Stabilator with Indicator
- Landing Gear, Retractable Electro-Hydraulic
- Landing Gear Selector Switch
- Landing Gear Warning Horn
- Landing Gear Emergency Extension
- Fuel Control Selector with On/Off/Cross feed
- Overhead Panel Switches:
 - Starter LH and RH
 - Fuel Pump LH and RH Ignition Switches
 - Right Engine LH and RH Ignition Switches

Electrical System

12 volt 35 AH GILL

12 volt alternator-40 amp, two

- Rocker switches internally lighted
 - Master switch
 - o Landing light
 - o Taxi light
 - Navigation lights
 - Strobe light
 - Pitot heat
 - Map light
- External power supply receptacle
- Circuit breaker panel
- Static discharge wicks

Fuel System

- Two Integral Fuel tank with 53 US Gal Total Capacity Engine Driven
- Fuel Pumps, Two Auxiliary Fuel
 Pumps, Electric Two Fuel Tank
- Quick Drain, Two Fuel Tank Quick
- Drain, Two 2x Shut Off Valves with
- Cross Feed

Interior

- Pilot and Co-Pilot Seats Simulated Leather
 - o Adjustable Fore and Aft
 - Electric Vertical Adjustment
- Rear Passenger Seats, Two
- Seat Belts & Shoulder Harness, all Seats
- Wall to wall Carpeting
- Fire Extinguisher
- Map & Storage Pockets
- Radio Call Plate
- Tow Bar
- Soundproofing
- Luggage Compartments
- Overhead Cockpit Speaker
- Four Position Intercom System
- First Aid Kit

Interior Lights

- Avionics Instruments Internally Lighted
- Avionics Radios Internally Lighted
- Engine Instruments Internally
- Lighted
 Flight Instruments Internally
- Lighted Compass Internally Lighted
- Map Light
- Dimmers

Exterior

- Epoxy Corrosion Proofing, All Structure
- LH Front Door Pilot/Co-Pilot, Lock & Key
- . RH Rear Door Passenger
- Rear Window
- All Windows Tinted
- Retractable Landing Gear
- Tie Down Rings
- Main Wheels, 6.00 X 6 Nose 5.00
- X 5

Exterior Lights

- Nav. Lights LED with Strobe Full LED TSO
- Vertical Tail Strobe
- Landing/Taxi Light LED

Product Support/Documents

- Manufacture's Full Two-Year Limited Warranty
 - Pilot's Operation Handbook
- Maintenance Manual
- Parts Catalog
- · Aircraft Logbook
- Engine Logbook
- Propeller Logbook

Cabin Comfort System

Windshield Defroster Ventilator adjustable, 4 Place Heating System

Powerplant and Propeller

- Engines 2 Rotax 912S3 100 Hp, 4 Cylinders Liquid/Air Cooled,
- Integrated Reduction Gear Dual Ignition System Throttle Control
- LH/RH Air Filter, Two Oil Filter, Two Oil and Water Coolers, Two Carburetor Heat with Manual
- Control
- •

Standard GARMIN Avionics

Package Includes:

- Altitude Encoder
- Avionics Master Switch
- Mic & Phone Jacks Pilot/Copilot/Passengers
- Hand Helad Microphone
- Avionics Cricut Breaker Panel
 Pilot and Copilot PTT
- ELT 406
- Antennas:
 - Maker Beacon Antenna
 - o Transponder Antenna
 - VHF & NAV Antenna
 - Emergency Locator Transmitter
 Antenna



Design Weight and Loading

Maximum Take Off Weight	2,712 lb	1,230 kg
Empty Weight, Standard	1,896 lb	860 kg
Useful Load	816 lb	370 kg
Baggage Allowance	176 lb	80 kg

Performance

Max Cruise Speed KTAS	145 kts	269 km/h
Stall Speed (Flaps Down Power Off) KCAS	55 kts	102 km/h
Max Operating Altitude	14,000 ft	4,267 m
Take off run	988 ft	301 m
Take off distance	1,293 ft	394 m
Rate of climb	1,036 ft/min	5.3 m/sec
Landing Run	758 ft	231 m
Landing Distance	1,145 ft	349 m
Range	650 nm	1,204 km

